

# Cupla metalica rapida Mama EUROLINE-arc pt furtun

Cupla metalica rapida Mama EUROLINE-arc pt furtun

112/D

112 D/1	Cupla rapida Mama EUROLINE-cu arc pt furtun Ø4×6
112 D/2	Cupla rapida Mama EUROLINE-cu arc pt furtun Ø6×8
112 D/3	Cupla rapida Mama EUROLINE-cu arc pt furtun Ø8×10

---

# Cupla metalica rapida Mama EUROLINE-filet exterior

Cupla metalica rapida Mama EUROLINE-filet exterior

112

112/1	Cupla rapida Mama EUROLINE- FE 1/4
112/2	Cupla rapida Mama EUROLINE- FE 3/8
112/3	Cupla rapida Mama EUROLINE- FE 1/2

---

# Cupla metalica rapida Mama EUROLINE-filet interior

Cupla metalica rapida Mama EUROLINE-filet interior

112/A

112/A1- cupla rapida mama filet interior 1/4

112/A2- cupla rapida mama filet interior 3/8

112/A3- cupla rapida mama filet interior 1/2


# Cupla metalica rapida Mama EUROLINE-racord furtun

Cupla metalica rapida Mama EUROLINE-racord furtun

112/B

112 B/1	Cupla rapida Mama EUROLINE-cu racord furtun Ø6×10
112 B/2	Cupla rapida Mama EUROLINE-cu racord furtun Ø6×12
112 B/3	Cupla rapida Mama EUROLINE-cu racord furtun Ø6×14
112 B/4	Cupla rapida Mama EUROLINE-cu racord furtun Ø8×12
112 B/5	Cupla rapida Mama EUROLINE-cu racord furtun Ø8×14
112 B/6	Cupla rapida Mama EUROLINE-cu racord furtun Ø8×17
112 B/7	Cupla rapida Mama EUROLINE-cu racord furtun Ø10×14,5

112 B/8	Cupla rapida Mama EUROLINE-cu racord furtun Ø10×17
112 B/9	Cupla rapida Mama EUROLINE-cu racord furtun Ø10×19

---

## **Cupla metalica rapida Mama EUROLINE-stut pt furtun**

Cupla metalica rapida Mama EUROLINE-stut pt furtun

112/C

112 C/1	Cupla rapida Mama EUROLINE-cu stut pt furtun Ø6
112 C/2	Cupla rapida Mama EUROLINE-cu stut pt furtun Ø8
112 C/3	Cupla rapida Mama EUROLINE-cu stut pt furtun Ø10

---

## **Cupla metalica rapida Mama Standard Sicomat-filet exterior**

Cupla metalica rapida Mama Standard Sicomat-filet exterior

112

112/1	Cupla rapida Mama EUROLINE- FE 1/4
-------	------------------------------------

112/2	Cupla rapida Mama EUROLINE- FE 3/8
112/3	Cupla rapida Mama EUROLINE- FE 1/2

Cuple rapide mama cu filet exterior 1/4", 3/8", 1/2" seria Standard Sicomat sunt compatibile cu racordurile tata standard italian, american, german, ceh

Beneficiaza de un strat protector din plastic, antisoc si antizgariere

Pot fi folosite pentru aer, apa si alte fluide neagresive

Temperatura optima de lucru -15/80°C, presiune maxima 16 bar

PN: 8 Bar